

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 784 738 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
20.05.1998 Bulletin 1998/21

(51) Int Cl.⁶: **F01N 3/02, F02M 45/02,
F02M 45/04, F02D 41/40**

(21) Application number: **95926484.7**

(86) International application number:
PCT/IT95/00124

(22) Date of filing: **21.07.1995**

(87) International publication number:
WO 96/03571 (08.02.1996 Gazette 1996/07)

(54) **METHOD OF AUTOMATICALLY INITIATING REGENERATION OF A PARTICULATE FILTER OF
A DIESEL ENGINE WITH A RAIL INJECTION SYSTEM**

**VERFAHREN ZUR AUTOMATISCHEN INITIALISIERUNG DER REGENERATION EINES
PARTIKELFILTERS EINES DIESELMOTORS MIT GEMEINSAMER BRENNSTOFFLEITUNG**

**PROCEDE D'AMOR AGE AUTOMATIQUE DE LA REGENERATION D'UN FILTRE A PARTICULES
DANS UN MOTEUR DIESEL A SYSTEME D'INJECTION A RAIL**

(84) Designated Contracting States:
DE ES FR GB IT SE

• **CANALE, Silvio**
I-10092 Collegno (IT)

(30) Priority: **22.07.1994 IT TO940606**

(74) Representative: **Jorio, Paolo et al**
STUDIO TORTA S.r.l.,
Via Viotti, 9
10121 Torino (IT)

(43) Date of publication of application:
23.07.1997 Bulletin 1997/30

(73) Proprietor: **C.R.F. Società Consortile per Azioni**
10043 Orbassano (TO) (IT)

(56) References cited:
EP-A- 0 070 619 EP-A- 0 411 445
EP-A- 0 621 400 DE-A- 4 117 676
DE-C- 3 729 857 JP-A- 5 156 993

(72) Inventors:
• **ROSSI SEBASTIANO, Giovanni, Maria**
I-10124 Torino (IT)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

TECHNICAL FIELD

The present invention relates to a method of automatically initiating regeneration of a particulate filter of a diesel engine, according to the preamble of claim 1.

BACKGROUND ART

As is known, to safeguard the environment, increasing effort is being made, and in many countries tighter restrictions are being imposed, to control the exhaust of internal combustion engines.

As regards diesel engines in particular, the main problems are due to the presence in the exhaust gas of nitric oxides (NO_x) and particulates, as opposed to a very low content of carbon monoxide (CO) and hydrocarbons (HC).

To minimize the particulate content of exhaust gas, some systems feature, along the exhaust line, a filter for retaining the unburned particles of which the particulate is composed, and which must therefore be cleaned ("regenerated") periodically by burning off the trapped particulate.

Since combustion of the particulate is naturally initiated automatically at high temperature - around 500-550°C - which is only reached in particular circumstances, some filters are fitted with heating elements which are activated periodically to heat the filter to the temperature at which combustion of the trapped particulate is initiated automatically. Other systems present a catalyst for reducing the initiating temperature to roughly 350°C, which solution, however, is only effective under medium engine load conditions. In the case of prolonged low-load operation of the engine (e.g. town driving) and/or in the presence of low external temperatures (in winter), the temperature of the exhaust gas is lower than the combustion initiating temperature, so that the particulate gradually builds up on the filter, thus resulting in increased counterpressure, impaired performance, increased fuel consumption and possibly even stalling of the engine.

Moreover, in certain driving conditions, a high build-up of particulate may result in "critical" regeneration phenomena, in turn resulting in sudden, uncontrolled combustion of the particulate, heating inside the ceramic matrix of the filter, and damage to the filter itself.

A method for regenerating a particulate filter of a diesel engine according to the preamble of claim 1 is disclosed in EP-A-0 070 619, wherein a post-injection phase is carried out directly in the cylinders in the exhaust stroke so as to supply unburnt fuel to the filter. Regeneration of the filter is effected without causing a rise in the exhaust gas temperature.

DISCLOSURE OF INVENTION

It is an object of the present invention to provide a method of automatically initiating combustion of the particulate trapped in the filter, even under engine load conditions in which the exhaust gas temperature is not guaranteed equal to or above the initiating temperature of known systems.

According to the present invention, there is provided a method of automatically initiating regeneration of a particulate filter of a diesel engine comprising a main injection phase and an auxiliary post-injection phase including injection of fuel into the engine cylinders during the expansion stroke of the engine, characterized in that the injection is carried out through a rail injection system so as to generate post-injected fuel combustion causing a rise in the exhaust gas temperature of the engine.

BRIEF DESCRIPTION OF DRAWINGS

A preferred, non-limiting embodiment of the present invention will be described by way of example with reference to the accompanying drawings, in which:

Figure 1 shows a block diagram of a known diesel engine injection system;

Figure 2 shows a graph of pressure and injection, in relation to the engine strokes, according to the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Figure 1 shows schematically a diesel engine rail injection system 1 of the type to which the present invention relates. Of system 1, only the parts pertinent to the present invention are shown, the fuel conduits being indicated by continuous lines, and the dotted lines indicating the electric lines supplying the control and measured quantity signals.

System 1 comprises:

- a fuel (diesel fuel) tank 2;
- a high-pressure supply pump 3 connected to tank 2 by a low-pressure conduit 4;
- a pressure regulator 6 along a high-pressure line 7;
- a low-pressure fuel return conduit 8 between pressure regulator 6 and tank 2;
- a high-pressure fuel rail 9 connected to conduit 7 and presenting one or more elements for connection to the injectors;
- a number of injectors 10 - one for each cylinder 11 of engine 12 - connected to rail 9;
- a power control unit (central control unit) 16 for governing the system components on the basis of signals from various sensors, memorized maps, and the control strategy implemented;
- a combustion product exhaust conduit 17 connected to the exhaust manifold (not shown) of engine

- 12;
- a particulate filter 18 on exhaust conduit 17;
- an intake manifold 19;
- a pressure sensor 20 on rail 9;
- a cycle sensor 21 on the camshaft (not shown) of engine 12;
- an engine speed and stroke sensor 22 on the output shaft 23 of the engine; and
- a pressure sensor 24 on exhaust conduit 17, upstream from particulate filter 18.

Pressure regulator 6, injectors 10, pressure sensor 20, cycle sensor 21, and engine speed and stroke sensor 22 are connected to central unit 16 over electric data and control exchange lines.

According to the present invention, in addition to the main injection phase controlled in the normal way by central unit 16, injection system 1 also provides for post-injecting fuel to increase the exhaust temperature of the engine and/or generate incomplete-combustion products (HC) for reducing the ignition temperature of the particulate accumulated on the filter, and so assisting low-temperature, low-engine-load regeneration of the filter.

The timing of the auxiliary post-injection phase is shown schematically in Figure 2 wherein a first graph shows the pressure at the various strokes of each cylinder; a second graph shows the location of the main injection (30) and post-injection (31) phases in three different cases; TDC indicates top dead center, BDC bottom dead center, IND the induction stroke, COMP the compression stroke, EXP the expansion stroke, and EX the exhaust stroke.

The dot-and-dash curve shows injection pressure under low engine load conditions; the dash-line curve injection pressure under medium engine load conditions; and the continuous-line curve injection pressure under medium-high engine load conditions. Similarly, timing of the main injection and post-injection phases in the above three cases is shown using the same graphic means: dot-and-dash line (low load), dash line (medium load), and continuous line (high load). The arrows to the right and left of the main injection and post-injection phases indicate the possibility of location and duration varying - being advanced, delayed, lengthened or shortened - as compared with the example shown, to take into account the operating conditions of the engine, and ensure the ignition temperature of the filter at the required conditions for optimizing engine consumption.

According to the invention, the post-injection phase comprises the injection of a given quantity of fuel-air mixture directly into the cylinders during the expansion stroke EXP, when the temperature in the combustion chamber is still high enough for its combustion. For this purpose, on the basis of filter clogging values (based on the counterpressure of the filter and on engine speed and load) and predetermined algorithms, central unit 16 determines when to perform the post-injection, and pos-

sibly also timing and quantity as a function of engine load and speed.

More specifically, the start angle is directly proportional to load (as shown by curve a) in Figure 2 relative to the lowest load) and the injected fuel quantity is inversely proportional to load. In general, post-injection may even be performed immediately following the main injection, as a single injection of a duration equal to the sum of the two; and the amount of post-injected fuel ranges from a few percent of the main injection (medium loads) to roughly 40-50% of the maximum main injection values relative to the engine speed in question.

According to one embodiment of the present invention, as opposed to being performed in all the cylinders at each cycle, post-injection is alternated from one cylinder to another at successive cycles, to balance the thermal load of the cylinders and so enable post-injection of smaller overall quantities than that which can be handled by the system with the same conditions existing in all the cylinders.

Also, depending on the operating conditions of engine 12, post-injection may be performed in a predetermined number of consecutive or nonconsecutive cycles.

Naturally, alternation of the cylinders, the post-injection enabling sequence in successive cycles, and the number of cycles in which post-injection is to be performed (overall duration) are memorized as a function of engine conditions in a storage element in or associated with central unit 16.

Post-injection may be performed in any of various ways. In a first solution, the operating load of the engine (normally already available for other processing functions) is monitored continuously to determine how long it remains below a predetermined limit value; and if the engine operates at less than full load beyond a predetermined time limit, the central unit enables the post-injection phase to initiate regeneration of the filter which is most likely clogged. In this case, the pressure sensor upstream from the filter may be dispensed with.

In a second solution, the post-injection phase is effected periodically, regardless of engine load, the premise being that, generally speaking, at low engine speed, the filter clogs after a predetermined operating time, so that initiating regeneration of the filter automatically at regular intervals ensures the filter operates under acceptable conditions. This solution is best suited to known, constant operating modes.

In a third solution, clogging of the filter is determined indirectly by monitoring, by means of sensor 24, the pressure upstream from the filter and which is correlated to the particulate buildup on the filter. In this case, central unit 16 provides for calculating clogging of the filter - normally expressed as a percentage - on the basis of a known algorithm, the variables of which also include engine speed and load, and enables the post-injection phase upon a predetermined percentage being reached.

In a fourth solution, a combined strategy is applied.

Clogging of the filter is monitored as in the third solution, and, upon a predetermined threshold being reached (e.g. 80%), the central unit switches to standby awaiting the right moment in which to perform the post-injection phase, e.g. an engine load below a predetermined value, and on determining such a load, enables the post-injection phase. Naturally, in this solution also, the central control unit continues to determine that clogging remains within a maximum permissible value, and, if this is exceeded, enables post-injection regardless of the operating load, to prevent damage to the filter and to minimize fuel consumption.

With an electronic rail injection system of the type described, the post-injection phase is performed with no difficulty by virtue of injection being controlled electronically by the control signals supplied by central unit 16 to injectors 10, and timing in relation to the engine strokes being fully flexible and in no way restricted by characteristics inherent in the system.

The advantages of the present invention are as follows. In particular, it provides for regenerating the particulate filter under engine conditions which in themselves would fail to do so. Moreover, though at first sight it may appear to increase fuel consumption, this is not so, by virtue of post-injection being performed when the filter is clogged (as detected on the basis of the low-speed operating time of the engine or the pressure upstream from the filter), i.e. when fuel consumption is already increased due to the condition of the filter. As post-injection provides for regenerating and hence improving the operating conditions of the filter, the increase in consumption due to the post-injection phase is more than compensated for by the reduction achieved by improving the operating conditions of the filter.

Moreover, the method according to the invention requires no special devices or alterations to the engine or injection system, but simply software control of the injector signals, so that it may be implemented easily and cheaply on existing electronic rail injection system control units.

Claims

1. A method of automatically initiating regeneration of a particulate filter of a diesel engine comprising a main injection phase and an auxiliary post-injection phase including injection of fuel into the engine cylinders during the expansion stroke of the engine, **characterized in that** the injection is carried out through a rail injection system so as to generate post-injected fuel combustion causing a rise in the exhaust gas temperature of the engine.
2. A method as claimed in Claim 1, characterized in that said post-injection phase is performed alternately in the engine cylinders in successive cycles.

3. A method as claimed in Claim 1 or 2, characterized in that it comprises the step of controlling said post-injection phase according to a memorized cycle sequence.
4. A method as claimed in any one of the foregoing Claims, characterized in that it provides for monitoring the conditions of the engine, and for enabling said post-injection phase upon detection of predetermined events continuing for a time in excess of a predetermined value.
5. A method as claimed in Claim 4, characterized in that said engine conditions comprise engine speed and load, and said events comprise engine speed and load falling below respective threshold values.
6. A method as claimed in Claim 4 or 5, characterized in that said engine conditions comprise the degree of clogging of said particulate filter, calculated as a function of the pressure upstream from said particulate filter, and of engine speed and load; and said events comprise said degree of clogging exceeding a respective threshold value.
7. A method as claimed in any one of the foregoing Claims from 1 to 3, characterized in that it provides for enabling said post-injection phase at predetermined operating time intervals.
8. A method as claimed in any one of the foregoing Claims, characterized in that said post-injection phase comprises the injection of a quantity of fuel as a function of engine load and speed.
9. A method as claimed in any one of the foregoing Claims, characterized in that said post-injection phase is delayed as a function of engine load and speed, in relation to said main injection phase.

Patentansprüche

1. Verfahren zum automatischen Beginnen der Regenerierung eines Feststoffteilchenfilters eines Dieselmotors, mit einer Haupteinspritzphase und einer zusätzlichen Nacheinspritzphase, in der während des Arbeitshubs des Motors ein Einspritzen von Treibstoff in die Motorzylinder erfolgt, dadurch gekennzeichnet, daß das Einspritzen über ein Rail-Einspritzsystem erfolgt, so daß eine Treibstoffverbrennung durch Nacheinspritzung ausgelöst wird, die ein Ansteigen der Abgastemperatur des Motors verursacht.
2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die Nacheinspritzphase in den Motorzylindern abwechselnd in aufeinanderfolgenden Zyklen

durchgeführt wird.

3. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß es die Stufe des Steuerns der Nacheinspritzphase gemäß einer gespeicherten Zyklussequenz umfaßt. 5
4. Verfahren nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß vorgesehen ist, die Motorbedingungen zu überwachen und die Nacheinspritzphase zu ermöglichen, wenn festgestellt wird, daß vorgegebene Ereignisse während einer Zeit andauern, die über einen vorgegebenen Wert hinausgeht. 10
5. Verfahren nach Anspruch 4, dadurch gekennzeichnet, daß die Motorbedingungen die Motordrehzahl und -last umfassen, und daß die Ereignisse die unter einen jeweiligen Schwellenwert fallende Motordrehzahl und -last umfassen. 15
6. Verfahren nach Anspruch 4 oder 5, dadurch gekennzeichnet, daß die Motorbedingungen den Verstopfungsgrad des Feststoffteilchenfilters, berechnet als Funktion des Drucks stromaufwärts von dem Feststoffteilchenfilter, sowie die Motordrehzahl und -last umfassen, und daß die Ereignisse den einen entsprechenden Schwellenwert überschreitenden Verstopfungsgrad umfassen. 20
7. Verfahren nach einem der vorstehenden Ansprüche 1 bis 3, dadurch gekennzeichnet, daß es vorsieht, daß die Nacheinspritzphase in vorgegebenen Betriebszeitintervallen stattfinden kann. 25
8. Verfahren nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß die Nacheinspritzphase das Einspritzen einer Treibstoffmenge als Funktion der Motorlast und -drehzahl umfaßt. 30
9. Verfahren nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß die Nacheinspritzphase als Funktion der Motorlast und -drehzahl in bezug auf die Haupteinspritzphase verzögert ist. 35

Revendications

1. Procédé d'amorçage automatique de la régénération d'un filtre à particules dans un moteur diesel comprenant une phase d'injection principale et une phase de post-injection auxiliaire comprenant l'injection de carburant dans les cylindres du moteur pendant la course de détente du moteur, caractérisé en ce que l'injection est réalisée au moyen d'un système d'injection à rail afin de générer une combustion de carburant post-injecté entraînant une 50

élévation de la température des gaz d'échappement du moteur.

2. Procédé selon la revendication 1, caractérisé en ce que ladite phase de post-injection est réalisée de manière alternée dans les cylindres du moteur au cours de cycles successifs.
3. Procédé selon la revendication 1 ou 2, caractérisé en ce qu'il comprend l'étape consistant à commander ladite phase de post-injection selon une séquence de cycles mémorisés.
4. Procédé selon l'une quelconque des revendications précédentes, caractérisé en ce qu'il procure une surveillance des états du moteur, et en ce qu'il permet ladite phase de post-injection lors de la détection d'événements prédéterminés continuant sur une durée dépassant une valeur prédéterminée.
5. Procédé selon la revendication 4, caractérisé en ce que lesdits états du moteur comprennent le régime et la charge du moteur, et lesdits événements comprennent le régime et la charge du moteur tombant au-dessous de valeurs de seuil respectives.
6. Procédé selon la revendication 4 ou 5, caractérisé en ce que lesdits états du moteur comprennent le degré d'obstruction dudit filtre à particules, calculé en fonction de la pression en amont dudit filtre à particules, et du régime et de la charge du moteur, et lesdits événements comprennent ledit degré d'obstruction dépassant une valeur de seuil respective.
7. Procédé selon l'une quelconque des revendications précédentes 1 à 3, caractérisé en ce qu'il permet ladite phase de post-injection à des intervalles de temps de fonctionnement prédéterminés.
8. Procédé selon l'une quelconque des revendications précédentes, caractérisé en ce que ladite phase de post-injection comprend l'injection d'une certaine quantité de carburant en fonction de la charge et du régime du moteur.
9. Procédé selon l'une quelconque des revendications précédentes, caractérisé en ce que ladite phase de post-injection est retardée en fonction de la charge et du régime du moteur, par rapport à ladite phase d'injection principale. 55




Fig. 1




Fig. 2